

SE192K ST441



110mm



70mm

80mm



GAS DETECTOR

- Degree of protection IP44
- Powered by the control unit
- Average Sensor life in clean air: 5 years
- Suitable for use with control panels: SE128K - SE194K - SE294

TECHNICAL DATA

CE IP44

Tecnocontrol's code: SE192

Geca's code: ST441

Range: 0 ÷ 20% LEL

| Code | Gas Detected | Sensor Type | Measuring Range | Power Supply | Electrical Input | Output | Calibration Cylinder | Average Sensor life in clean air | Maximum Storage Time |
|--------------------|--------------|-------------|-----------------|---------------------|------------------|---------|----------------------|----------------------------------|----------------------|
| SE192KM ST441KM | Methane | Catalytic | 0÷20% LEL | 12Vdc (-10/+15%) | 1 W | 4÷20 mA | B0006 | 5 years | 5 years |
| SE192KG ST441KM | LPG | Catalytic | 0÷20% LEL | | 1 W | 4÷20 mA | B0006 | 5 years | 5 years |

SE301



200mm



80mm

150mm



SIREN

Piezoelectric modulated siren with flashing red light indication.

CE IP44

| Code | Power Supply | Absorption | Sound intensity | Installation | Degree of Protection | Lighting |
|--------|-----------------|----------------------------|-----------------|--------------|----------------------|----------|
| SE301A | 230Vca 12Vdc | 9VA - 230Vac 6W - 12Vdc | 115 db | Wall | IP44 | LED |