



Product Code	771788R, 771788B , 771789R, 771789B, 771790R, 771790B
Description	INSTANTOR® IMPERIAL CxC FULL BORE COPPER ALLOY LEVER ACTION BALL VALVES
Size Range	½" , ¾" & 1" CxC with Gland nut and with Red or Blue Coloured PVC Handles
Max Operating Pressure	25 Bar
Min Operating Pressure	0 Bar
Max Operating Temperature	85°C. With short term excursions of 95°C (less than 1 hour)
Min Operating Temperature	-20°C
Material Specification	EN12165 CW617N DW Brass – Plated, EDPM O-rings and with PTFE seals.
To Standard:	Compression Ends to I.S.E.N:1254-2:1998 WRAS Cert No. 1904354. & KIWA Cert No. 1904751. Water fittings Regulation 1999

Valves up to 1" and with a maximum allowable pressure greater than 0.5Bar regarding liquids-fall under the Sound Engineering Practices (SEP – Article 4, section 3) and do not require CE certification or Declaration of conformity under the Pressure Equipment Directive (2014/68/EU)

T: 01 842 6255 E: sales@sanbra.ie www.sanbra.ie

Sanbra Fyffe Ltd

Instantor Works, Santry Avenue, Santry, Dublin D09 K160

